پلی استایرن معمولی (GPPS) 1551 کریستال تولید کننده: پتروشیمی تندگویان





Takht-e-Jamshid Pars Assalouyeh Petrochemical Company

	General Purpo	ose Polystyrene (GPPS)	
TYPICAL DATA SHEET	GRADE	www.tjpa-pc.com	
	TJPS-G1551 (Normal flow)	IRAN/ASSALOUYEH/PETROCHEMICAL COMPANY/ TEL: +98-(21)-91008030	

This grade is high strength & high cycle polystyrene.

Main Applications:

Thin walled food Containers, Medical ware (petri dishes etc), Office stationary, housewares, etc.

TECHNICAL SPECIFICATION

PROPERTIES	UNIT	VALUE	STANDARD
Tensile Strength (Yield)	(kg/cm²)	440	D-638
Tensile Modulus of Elasticity	(kg/cm²)	2.6×10 ⁴	D-638
Izod Impact Strength (notched,t=6.4 mm)	(kg-cm/cm)	2.4	D-256
Vicat Softening Point (50°C/hr ,1000 g)	(°C)	92	D-1525
Melt Index (200°C, 5000 g)	(g/10 min)	9	D-1238

^{*}All above mentioned data are typical values and not to be construed as real specifications. Users should confirm results by their own tests. Which is included MFI and Vicat.

^{**} TJPAPC Guaranteed items are MFI and Vicat .